



The VA-2060 is a digital networked two-channel amplifier for use in Vocia systems. It is capable of delivering continuous audio power at 60 Watts RMS per channel. The VA-2060 is CobraNet® enabled for audio and control with dynamic use of bundles. Two RJ45 connectors on the rear panel provide redundant CobraNet connectivity to the Vocia network. The on-board DSP provides comprehensive fixed-chain, digital signal processing within the device. In addition, emergency messages can be stored in local non-volatile memory. Page active relay outputs provide a contact closure per channel when paging is active on the channel. The amplifier offers low impedance and constant voltage outputs. The VA-2060 also has comprehensive failover capability with device-to-device and channel-to-channel failover.

FEATURES

- Two channels of 60W RMS per channel
- Transformer coupled outputs, low impedance (4 or 8Ω) or 25V, 70V or 100V (hardware selectable)
- Comprehensive failover
 - o Device-to-device
 - o All-to-1 channel
 - o 1:1 channel
- Supports Page Active Relay (PAR), ELD-1 and ANC-1
- Local non-volatile storage of emergency messages
- LED status and signal indication
- Software-configurable signal processing including volume control, filters, compressor/limiting, delay, speaker equalization and output sensitivity
- CobraNet audio/control with dynamic use of available bundles
- Dual Ethernet ports for redundancy
- Rotary switches for device identification
- Rack mountable (2RU)
- EN 54-16 certified, CE marked, UL listed and RoHS compliant
- Covered by Biamp Systems' warranty

ARCHITECTS & ENGINEERS SPECIFICATION

The networked amplifier shall be designed exclusively for use with Biamp® Vocia® systems. The amplifier shall support 2 channels of 60 Watts RMS per channel and 25V, 70V and 100V transformer-coupled capability, or low-impedance (4 or 8Ω) operation. The amplifier shall provide control data and digital audio over CobraNet®. The amplifier shall provide dual Ethernet ports for redundant network connection. The amplifier shall provide front panel LED identification of amplifier and card failure, signal present, clip present, fan stuck rotor fault, heat sink temperature fault and provide additional software monitoring features including short circuit on output fault. The amplifier shall be rack mountable (2RU) and feature software-configurable signal processing including volume control, filters, compressor/limiting, delay, speaker equalization and output sensitivity. The amplifier shall support channel-to-channel and chassis-to-chassis failover. The amplifier is EN 54-16 certified, shall be CE marked and UL listed and shall be compliant with the RoHS directive. Warranty shall be five years. The amplifier shall be a Vocia VA-2060.

Vocia Amplifier VA-2060 SPECIFICATIONS

Memory:	5.625 MB	Power:	100-240VAC; 50/60Hz
Inputs:	20 bits, 48 kHz, 5-1/3 ms (fixed)	Overall Dimensions:	
		Height:	3.25 inches (82.5 mm)
		Width:	19.0 inches (483 mm)
		Depth:	14.2 inches (361 mm)
Frequency Response:	40Hz-20kHz +/- 2dB	Weight:	24.7 lbs (11.2 kg)
Signal to Noise Ratio:	>88dB, unweighted	Compliance:	EN 54-16 certified
			FCC Part 15B
			CE marked
			UL 60065 and C-UL listed
			CCC pending
			C-Tick
			RoHS Directive
			EN 60849, AS 60849 verified
Connections:	Network: RJ45 with shielded Ethernet (Cat5, Cat5e, Cat6 or Cat7)		
Total Output Power:	2 x 60W RMS, 120W maximum		
Environment:	Ambient Operating Temperature Range: 26-107 degrees F (-3°C to 42°C) Ambient intake humidity: 0-100% (non-condensing) Altitude: 0-10,000 Feet MSL (0-3,000m)		

Vocia Amplifier VA-2060 BACK PANEL

